

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

1N3062
1N3063
1N3064

SILICON SWITCHING DIODE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N3062 Series types are very high speed Silicon Switching Diodes designed for computer and general purpose applications.

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

	SYMBOL	1N3062	1N3063	1N3064	UNIT
Peak Repetitive Voltage	V_{RRM}	75	75	75	V
Peak Working Reverse Voltage	V_{RWM}	50	50	50	V
Average Forward Current	I_O	75	75	75	mA
Forward Steady-State Current	I_F	115	115	115	mA
Peak Forward Current (Recurrent)	I_{FM}	225	225	225	mA
Peak Forward Surge Current (1.0 μ s)	I_{FSM}	2000	2000	2000	mA
Power Dissipation	P_D	250	250	250	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 TO +200			$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I_R	$V_R=50\text{V}$		0.1	μA
I_R	$V_R=50\text{V}, T_A=150^{\circ}\text{C}$		100	μA
BV_R	$I_R=5.0\mu\text{A}$	75		V
V_F	$I_F=250\mu\text{A}$	0.505	0.575	V
V_F	$I_F=1.0\text{mA}$	0.55	0.65	V
V_F	$I_F=2.0\text{mA}$	0.61	0.71	V
V_F	$I_F=10\text{mA}$ (1N3064)	-	1.0	V
V_F	$I_F=10\text{mA}$ (1N3063)	0.7	0.85	V
V_F	$I_F=20\text{mA}$ (1N3062)	-	1.0	V
C_T	$V_R=0\text{V}, f=1.0\text{MHz}$ (1N3062)		1.0	pF
C_T	$V_R=0\text{V}, f=1.0\text{MHz}$ (1N3063, 1N3064)		2.0	pF
t_{rr}	$V_F=6.0\text{V}, I_F=10\text{mA}, R_L=100\Omega$ (1N3062)		2.0	ns
t_{rr}	$V_F=1.0\text{V}, I_F=10\text{mA}, R_L=100\Omega$ (1N3063, 1N3064)		4.0	ns
RE	$f=1.0\text{MHz}$	45		%
$\Delta V_F/^{\circ}\text{C}$			1.8	mV/ $^{\circ}\text{C}$

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms