


2N6071, A, B
2N6073, A, B
2N6075, A, B

SENSITIVE GATE TRIAC
4.0 AMPS, 200 THRU 600 VOLTS



TO-126 CASE

CentralTM
Semiconductor Corp.

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N6071, A, B series types are silicon sensitive gate triacs designed for such applications as light dimmers, motor controls, heating controls and power supplies.

MARKING CODE: FULL PART NUMBER

MAXIMUM RATINGS: ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

		2N6071 2N6071A 2N6071B	2N6073 2N6073A 2N6073B	2N6075 2N6075A 2N6075B	UNITS
Peak Repetitive Off-State Voltage	V_{DRM}, V_{RRM}	200	400	600	V
RMS On-State Current ($T_C=85^{\circ}\text{C}$)	$I_T(\text{RMS})$		4.0		A
Peak One Cycle Surge (60Hz, $T_J=110^{\circ}\text{C}$)	I_{TSM}		30		A
I^2t Value for Fusing ($t=8.3\text{ms}$)	I^2t		3.7		A^2s
Peak Gate Power ($T_C=85^{\circ}\text{C}$)	P_{GM}		10		W
Average Gate Power ($t=8.3\text{ms}$, $T_C=85^{\circ}\text{C}$)	$P_{G(AV)}$		0.5		W
Peak Gate Voltage ($T_C=85^{\circ}\text{C}$)	V_{GM}		5.0		V
Storage Temperature	T_{stg}		-40 to +150		$^{\circ}\text{C}$
Junction Temperature	T_J		-40 to +110		$^{\circ}\text{C}$
Thermal Resistance	θ_{JC}		3.5		$^{\circ}\text{C/W}$
Thermal Resistance	θ_{JA}		75		$^{\circ}\text{C/W}$
Maximum Lead Temperature	T_L		260		$^{\circ}\text{C}$


ELECTRICAL CHARACTERISTICS: ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	A Series		B Series		UNITS
		TYP	MAX	TYP	MAX	
I_{DRM}, I_{RRM}	$V_D=\text{Rated } V_{DRM}, V_{RRM}, T_J=25^{\circ}\text{C}$	10	10	10		μA
I_{DRM}, I_{RRM}	$V_D=\text{Rated } V_{DRM}, V_{RRM}, T_J=110^{\circ}\text{C}$	2.0	2.0	2.0		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD I}, T_J=25^{\circ}\text{C}$	30	5.0	3.0		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD II}, T_J=25^{\circ}\text{C}$	-	5.0	3.0		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD III}, T_J=25^{\circ}\text{C}$	30	5.0	3.0		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD IV}, T_J=25^{\circ}\text{C}$	-	10	5.0		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD I}, T_J=-40^{\circ}\text{C}$	60	20	15		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD II}, T_J=-40^{\circ}\text{C}$	-	20	15		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD III}, T_J=-40^{\circ}\text{C}$	60	20	15		mA
I_{GT}	$V_D=12\text{V}, R_L=100\Omega, \text{QUAD IV}, T_J=-40^{\circ}\text{C}$	-	30	20		mA
I_H	$V_D=12\text{V}, I_T=1.0\text{A}, T_J=25^{\circ}\text{C}$	30	15	15		mA
I_H	$V_D=12\text{V}, I_T=1.0\text{A}, T_J=-40^{\circ}\text{C}$	70	30	30		mA
V_{GT}	$V_D=12\text{V}, R_L=100\Omega, T_J=25^{\circ}\text{C}, \text{QUAD I, II, III, IV}$	2.0	2.0	2.0		V
V_{GT}	$V_D=12\text{V}, R_L=100\Omega, T_J=-40^{\circ}\text{C}, \text{QUAD I, II, III, IV}$	2.5	2.5	2.5		V
V_{TM}	$I_{TM}=6.0\text{A}$	2.0	2.0	2.0		V
t_{on}	$I_{TM}=14\text{A}, I_{GT}=100\text{mA}$	1.5	1.5	1.5		μs
dv/dt	$V_D=\text{Rated } V_{DRM}, I_{TM}=5.7\text{A}, T_J=85^{\circ}\text{C}$	5.0	5.0	5.0		$\text{V}/\mu\text{s}$

R0 (27-April 2004)

SENSITIVE GATE TRIAC
4.0 AMPS, 200 THRU 600 VOLTS

TO-126 CASE - MECHANICAL OUTLINE



LEAD CODE:

- 1) MT1
- 2) MT2
- 3) GATE

MARKING CODE:

FULL PART NUMBER

SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.094	0.110	2.40	2.80
B	0.050		1.27	
C	0.015	0.030	0.38	0.75
D	0.291	0.335	7.40	8.50
E	0.148		3.75	
F	0.118	0.134	3.00	3.40
G	0.413	0.472	10.50	12.00
H	0.618		15.70	
J	0.024	0.035	0.62	0.90
K	0.089		2.25	
L	0.177		4.50	
M	0.045	0.055	1.14	1.40
N	0.083		2.10	

TO-126 (REV:R3)

R0 (27-April 2004)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centalsemi.com

Worldwide Field Representatives:
www.centalsemi.com/wwreps

Worldwide Distributors:
www.centalsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centalsemi.com/terms



<http://www.centrasemi.com>

Product End of Life Notification

PDN ID:	PDN01148
Notification Date:	6/02/20
Last Buy Date:	12/02/20
Last Shipment Date	6/02/21

Summary: The 2N6071 series of SCRs in the TO-126 case is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

Central Part Number	Replacement
2N6071A	N/A, Stock Only
2N6071B	N/A, Stock Only
2N6073	N/A, Stock Only
2N6073A	N/A, Stock Only
2N6073B	N/A, Stock Only
2N6075A	N/A, Stock Only
2N6075B	N/A, Stock Only

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centrasemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.