| | 2N6552 | 2N6553 | NPN |
|---|--------|--------|-----|
| | 2N6555 | 2N6556 | PNP |
| • | | | S |



Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N6551, 2N6554 series types are complementary silicon transistors manufactured by the epitaxial planar process, designed for general purpose audio amplifier applications.

MARKING: FULL PART NUMBER

| MAXIMUM RATINGS: (T _A =25°C) Collector-Base Voltage Collector-Emitter Voltage | SYMBOL V _{CBO} V _{CEO} | 2N6551 <u>2N6554</u> 60 60 | 2N6552 <u>2N6555</u> 80 80 | 2N6553 <u>2N6556</u> 100 100 | UNITS V V |
|--|--|--|--|--|-----------------|
| Emitter-Base Voltage | V _{EBO} | | 5.0 | | V |
| Continuous Collector Current | Ι _C | | 1.0 | | А |
| Peak Collector Current | ICM | | 2.0 | | А |
| Continuous Base Current | Ι _Β | | 0.1 | | А |
| Power Dissipation | PD | | 2.0 | | W |
| Power Dissipation (T _C =25°C) | PD | | 10 | | W |
| Operating and Storage Junction Temperature | TJ, Tstg | | -65 to +150 |) | °C |
| Thermal Resistance | Θ_{JA} | | 62.5 | | °C/W |
| Thermal Resistance | Θ^{JC} | | 12.5 | | °C/W |


| ELECTRICAL | CHARACTERISTICS: (T _A =25°C) | | 6551 6554 | | 6552 6555 | | 6553 6556 | |
|-----------------------|---|-----|--------------|-----|--------------|-----|--------------|---------------------|
| SYMBOL | TEST CONDITIONS | MIN | MAX | MIN | MAX | MIN | MAX | UNITS |
| ICBO | V _{CB} =40V | - | 100 | - | - | - | - | nA |
| ICBO | V _{CB} =60V | - | - | - | 100 | - | - | nA |
| ICBO | V _{CB} =80V | - | - | - | - | - | 100 | nA |
| IEBO | V _{EB} =4.0V | - | 100 | - | 100 | - | 100 | nA |
| BVCBO | I _C =100μΑ | 60 | - | 80 | - | 100 | - | V |
| BVCEO | I _C =1.0mA | 60 | - | 80 | - | 100 | - | V |
| BVEBO | I _E =100μA | 5.0 | - | 5.0 | - | 5.0 | - | V |
| V _{CE(SAT)} | I _C =250mA, I _B =10mA | - | 0.5 | - | 0.5 | - | 0.5 | V |
| V _{CE} (SAT) | I _C =1.0A, I _B =100mA | - | 1.0 | - | 1.0 | - | 1.0 | V |
| V _{BE(ON)} | V _{CE} =5.0V, I _C =250mA | - | 1.2 | - | 1.2 | - | 1.2 | V |
| h _{FE} | V _{CE} =1.0V, I _C =10mA | 60 | - | 60 | - | 60 | - | |
| h _{FE} | V _{CE} =1.0V, I _C =50mA | 80 | 300 | 80 | 300 | 80 | 300 | |
| h _{FE} | V _{CE} =1.0V, I _C =250mA | 60 | - | 60 | - | 60 | - | |
| h _{FE} | V _{CE} =1.0V, I _C =500mA | 25 | - | 25 | - | 25 | - | |
| fт | V _{CE} =5.0V, I _C =100mA, f=20MHz | 75 | 375 | 75 | 375 | 75 | 375 | MHz |
| Cob | V _{CB} =20V, I _E =0, f=1.0MHz | - | 18 | - | 18 | - | 18 | pF |
| | | | | | | | R | 1 (23-January 2012) |



2N6551 2N6552 2N6553 NPN 2N6554 2N6555 2N6556 PNP

> COMPLEMENTARY SILICON TRANSISTORS

TO-202 CASE - MECHANICAL OUTLINE



| LEAD CODE: |
|------------------------|
| 1) Emitter |
| 2) Base |
| 3) Collector |
| Tab is common to pin 3 |

MARKING: FULL PART NUMBER

| DIMENSIONS | | | | |
|------------------|-------|-------|-------------|----------------|
| | INC | HES | MILLIMETERS | |
| SYMBOL | MIN | MAX | MIN | MAX |
| А | 0.055 | 0.071 | 1.40 | 1.80 |
| В | 0.016 | 0.024 | 0.40 | 0.60 |
| С | 0.173 | 0.181 | 4.40 | 4.60 |
| D | 0.374 | 0.413 | 9.50 | 10.5 |
| E | 0.118 | 0.154 | 3.00 | 3.90 |
| F (DIA) | 0.124 | 0.150 | 3.15 | 3.80 |
| G | 0.035 | 0.055 | 0.90 | 1.40 |
| Н | 0.023 | 0.031 | 0.59 | 0.80 |
| J | 0.094 | 0.106 | 2.39 | 2.69 |
| K | 0.459 | 0.559 | 11.66 | 14 <u>.</u> 21 |
| L | 0.280 | 0.346 | 7.12 | 8.80 |
| М | 0.406 | 0.531 | 10.3 | 13.5 |
| N | 0.024 | 0.059 | 0.60 | 1.50 |
| TO-202 (REV: R2) | | | | |

R1 (23-January 2012)

www.centralsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- · Consolidated shipping options

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

ss your design challenges.

· Custom product packing

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits

Custom bar coding for shipments

Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>





Product End of Life Notification

| PDN ID: | PDN01270 |
|--------------------|------------|
| Notification Date: | 5/30/24 |
| Last Buy Date: | |
| Last Shipment Date | Stock Only |

https://www.centralsemi.com

Please be advised that Central Semiconductor must immediately discontinue the product(s) listed in the attached PDN notice. Orders can only be accepted for products with available inventory on hand.

You may have purchased one or more of the products listed. Please do not hesitate to contact your local Central Semiconductor sales representative with any questions or needs you may have. Central regrets any inconvenience this may cause.

Sincerely,

Central Semiconductor, LLC

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



Product End of Life Notification

| PDN ID: | PDN01270 |
|--------------------|------------|
| Notification Date: | 5/30/24 |
| Last Buy Date: | |
| Last Shipment Date | Stock Only |

Summary:All devices manufactured in the TO-202 and TO-202-2 packages are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Portfolio Management. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

| Central Part Number | Suggested Replacement |
|---------------------|-----------------------|
| CEN-U01A | N/A |
| CEN-U02 | N/A |
| CEN-U05 | N/A |
| CEN-U05N | N/A |
| CEN-U06 | N/A |
| CEN-U06N | N/A |
| CEN-U07 | N/A |
| CEN-U07 MOD1 | N/A |
| CEN-U07N | N/A |
| CEN-U10 | N/A |
| CEN-U10N | N/A |
| CEN-U45 | N/A |
| CEN-U45N | N/A |
| CEN-U51A | N/A |
| CEN-U52 | N/A |
| CEN-U55 | N/A |
| CEN-U55N | N/A |
| CEN-U56 | N/A |
| CEN-U56N | N/A |
| CEN-U57 | N/A |
| CEN-U57N | N/A |
| CEN-U60 | N/A |
| CEN1314 | N/A |
| CEN1319 | N/A |
| CEN621 | N/A |
| CEN928 | N/A |
| CEN934 | N/A |
| D40C1 | N/A |
| D40C1N | N/A |
| D40C2 | N/A |
| D40C4 | N/A |
| D40C4N | N/A |
| D40C5 | N/A |
| D40C7 | N/A |
| D40C8 | N/A |
| *** CONTINUED *** | |
| | |

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

*:



https://www.centralsemi.com

Product End of Life Notification

| PDN ID: | PDN01270 |
|--------------------|------------|
| Notification Date: | 5/30/24 |
| Last Buy Date: | |
| Last Shipment Date | Stock Only |

*** CONTINUED FROM PRIOR PAGE ***

* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

| Central Part Number | Suggested Replacement |
|---------------------|-----------------------|
| D40D1 | N/A |
| D40D10 | N/A |
| D40D11 | N/A |
| D40D13 | N/A |
| D40D2 | N/A |
| D40D4 | N/A |
| D40D5 | N/A |
| D40D7 | N/A |
| D40D8 | N/A |
| D40E1 | N/A |
| D40E5 | N/A |
| D40E7 | N/A |
| D40K1 | N/A |
| D40K2 | N/A |
| D40K3 | N/A |
| D40K4 | N/A |
| D41D1 | N/A |
| D41D10 | N/A |
| D41D11 | N/A |
| D41D2 | N/A |
| D41D4 | N/A |
| D41D5 | N/A |
| D41D5 MOD | N/A |
| D41D7 | N/A |
| D41D8 | N/A |
| D41E1 | N/A |
| D41E5 | N/A |
| D41E7 | N/A |
| D41E7N | N/A |
| 2N6548 | N/A |
| 2N6549 | N/A |
| 2N6551 | N/A |
| 2N6552 | N/A |
| 2N6553 | N/A |
| 2N6554 | N/A |
| 2N6554-N | N/A |
| 2N6555 | N/A |
| 2N6556 | N/A |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit https://my.centralsemi.com/submit-inquiry?type=ER to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.