

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N930
2N930A

NPN SILICON TRANSISTOR

JEDEC TO-18 CASE

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N930, 2N930A types are Silicon NPN Planar Epitaxial Transistors designed for small signal general purpose and amplifier applications.

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)


| | SYMBOL | 2N930 | 2N930A | UNITS |
|---|----------------|-------------|--------|--------------------|
| Collector-Base Voltage | V_{CBO} | 45 | 60 | V |
| Collector-Emitter Voltage | V_{CEO} | 45 | 45 | V |
| Emitter-Base Voltage | V_{EBO} | 5.0 | 6.0 | V |
| Collector Current | I_C | 30 | | mA |
| Power Dissipation | P_D | 500 | | mW |
| Power Dissipation ($T_C=25^\circ\text{C}$) | P_D | 1.2 | | W |
| Operating and Storage Junction Temperature | T_J, T_{stg} | -65 to +200 | | $^\circ\text{C}$ |
| Thermal Resistance | θ_{JA} | 350 | | $^\circ\text{C/W}$ |
| Thermal Resistance | θ_{JC} | 146 | | $^\circ\text{C/W}$ |

ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

| SYMBOL | TEST CONDITIONS | 2N930 | | 2N930A | | UNITS |
|---------------|--|-------|-----|--------|-----|---------------|
| | | MIN | MAX | MIN | MAX | |
| I_{CBO} | $V_{CB}=45\text{V}$ | | 10 | | 2.0 | nA |
| I_{CES} | $V_{CE}=45\text{V}$ | | 10 | | 2.0 | nA |
| I_{CES} | $V_{CE}=45\text{V}, T_A=170^\circ\text{C}$ | | 10 | | 2.0 | μA |
| I_{CEO} | $V_{CE}=5.0\text{V}$ | | 2.0 | | 2.0 | nA |
| I_{EBO} | $V_{EB}=5.0\text{V}$ | | 10 | | 2.0 | nA |
| BV_{CBO} | $I_C=10\mu\text{A}$ | 45 | | 60 | | V |
| BV_{CEO} | $I_C=10\text{mA}$ | 45 | | 45 | | V |
| BV_{EBO} | $I_E=10\mu\text{A}$ | 5.0 | | 6.0 | | V |
| $V_{CE(SAT)}$ | $I_C=10\text{mA}, I_B=0.5\text{mA}$ | | 1.0 | | 0.5 | V |
| $V_{BE(SAT)}$ | $I_C=10\text{mA}, I_B=0.5\text{mA}$ | 0.6 | 1.0 | 0.7 | 0.9 | V |
| h_{FE} | $V_{CE}=5.0\text{V}, I_C=1.0\mu\text{A}$ | | | 60 | | |
| h_{FE} | $V_{CE}=5.0\text{V}, I_C=10\mu\text{A}$ | 100 | 300 | 100 | 300 | |
| h_{FE} | $V_{CE}=5.0\text{V}, I_C=10\mu\text{A}, T_A=-55^\circ\text{C}$ | 20 | | 30 | | |
| h_{FE} | $V_{CE}=5.0\text{V}, I_C=500\mu\text{A}$ | 150 | | | | |
| h_{FE} | $V_{CE}=5.0\text{V}, I_C=10\text{mA}$ | | 600 | | 600 | |
| f_T | $V_{CE}=5.0\text{V}, I_C=500\mu\text{A}, f=30\text{MHz}$ | 30 | | 45 | | MHz |
| C_{ob} | $V_{CB}=5.0\text{V}, I_E=0, f=1.0\text{MHz}$ | | 8.0 | | 6.0 | pF |
| NF | $V_{CE}=5.0\text{V}, I_C=10\mu\text{A}, R_S=10\text{k}\Omega, f=1.0\text{kHz}$ | | 3.0 | | 3.0 | dB |

JEDEC TO-18 CASE - MECHANICAL OUTLINE

All Dimensions in Inches (mm).



LEAD CODE:

- 1) EMITTER
- 2) BASE
- 3) COLLECTOR

CentralTM
Semiconductor Corp.

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms



<https://www.centalsemi.com>

Product End of Life Notification

| | |
|--------------------|----------|
| PDN ID: | PDN01269 |
| Notification Date: | 2/04/25 |
| Last Buy Date: | 8/04/25 |
| Last Shipment Date | 2/04/26 |

Summary: The following Small Signal transistors are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Portfolio Management. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

*** All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.**

| Central Part Number | Suggested Replacement |
|---------------------|-----------------------|
| BCV72 BK | N/A |
| BCV72 TR | N/A |
| BCY58-VII | N/A |
| BCY59 | N/A |
| BCY59-VII | N/A |
| BC107A | N/A |
| BC848A TR | N/A |
| CMPT930 BK | N/A |
| CMPT930 TR | N/A |
| MPS3393 | N/A |
| MPS3707 | N/A |
| MPS3710 | N/A |
| MPS6520 | N/A |
| MPS6520 APM | N/A |
| MPS6520 TRE | N/A |
| PE4001 | N/A |
| PE4001-18 | N/A |
| PN3565 | N/A |
| PN3565 APM | N/A |
| PN3565 TRE | N/A |
| PN3565-18 | N/A |
| PN930 | N/A |
| 2N2923 | N/A |
| 2N2923 APM | N/A |
| 2N2923 TRE | N/A |
| 2N2924 | N/A |
| 2N2924 APM | N/A |
| 2N2924 TRE | N/A |
| 2N2926 | N/A |
| 2N2926 APM | N/A |
| 2N2926 TRE | N/A |
| 2N3392 | N/A |
| 2N3392 APM | N/A |
| 2N3392 TRE | N/A |
| 2N3393 | N/A |
| 2N3393 APM | N/A |

*** CONTINUED ***

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



<https://www.centrasemi.com>

Product End of Life Notification

| | |
|--------------------|----------|
| PDN ID: | PDN01269 |
| Notification Date: | 2/04/25 |
| Last Buy Date: | 8/04/25 |
| Last Shipment Date | 2/04/26 |

*** CONTINUED FROM PRIOR PAGE ***

* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

| Central Part Number | Suggested Replacement |
|---------------------|-----------------------|
| 2N3393 TRE | N/A |
| 2N3397 | N/A |
| 2N3414 | N/A |
| 2N3416 | N/A |
| 2N3416 APM | N/A |
| 2N3416 APP | N/A |
| 2N3416 TRA | N/A |
| 2N3416 TRE | N/A |
| 2N3709 | N/A |
| 2N5172 | N/A |
| 2N5172 APM | N/A |
| 2N5172 TRE | N/A |
| 2N5209 | N/A |
| 2N5209 APM | N/A |
| 2N5209 TRE | N/A |
| 2N5961 | N/A |
| 2N5961 APM | N/A |
| 2N5961 TRE | N/A |
| 2N930 | N/A |
| 2N930A | N/A |
| 2N930B | N/A |
| 2SC1815 | N/A |
| 2SC1815 APM | N/A |
| 2SC1815 TRE | N/A |
| 2SC1815-BL | N/A |
| 2SC1815-GR | N/A |
| 2SC1815-O | N/A |
| 2SC1815-Y | N/A |
| 2SC1815-Y APM | N/A |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit <https://my.centrasemi.com/submit-inquiry?type=ER> to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.