

BUY49S
HIGH VOLTAGE
NPN SILICON TRANSISTOR



TO-39 CASE



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR BUY49S is a NPN Silicon Transistor designed for high voltage, high current applications.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: ($T_C=25^\circ\text{C}$)

Collector-Base Voltage
Collector-Emitter Voltage
Emitter-Base Voltage
Continuous Collector Current
Peak Collector Current
Power Dissipation ($T_A=25^\circ\text{C}$)
Operating and Storage Junction Temperature
Thermal Resistance
Thermal Resistance

SYMBOL		UNITS
V_{CBO}	250	V
V_{CEO}	200	V
V_{EBO}	6.0	V
I_C	3.0	A
I_{CM}	5.0	A
P_D	1.0	W
T_J, T_{stg}	-65 to +200	$^\circ\text{C}$
θ_{JC}	15	$^\circ\text{C/W}$
θ_{JA}	175	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS: ($T_C=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I_{CBO}	$V_{CB}=200\text{V}$		0.1	μA
I_{CBO}	$V_{CB}=200\text{V}, T_C=150^\circ\text{C}$		50	μA
BV_{CBO}	$I_C=100\mu\text{A}$	250		V
BV_{CEO}	$I_C=20\text{mA}$	200		V
BV_{EBO}	$I_E=1.0\text{mA}$	6.0		V
$V_{CE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$		0.2	V
$V_{BE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$		1.1	V
h_{FE}	$V_{CE}=5.0\text{V}, I_C=20\text{mA}$	40		
h_{FE}	$V_{CE}=5.0\text{V}, I_C=500\text{mA}$	40		
h_{FE}	$V_{CE}=2.0\text{V}, I_C=20\text{mA}, T_C=-55^\circ\text{C}$	16		
f_T	$V_{CE}=10\text{V}, I_C=100\text{mA}$	50		MHz
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1.0\text{MHz}$		30	pF
t_{on}	$V_{CC}=20\text{V}, I_C=500\text{mA}, I_{B1}=I_{B2}=50\text{mA}$		0.3	μs
t_{off}	$V_{CC}=20\text{V}, I_C=500\text{mA}, I_{B1}=I_{B2}=50\text{mA}$		1.0	μs
$I_{S/B}^*$	$V_{CE}=50\text{V}$	0.2		A


* Pulsed: 1.0s non repetitive pulse.

R0 (27-August 2010)

BUY49S
HIGH VOLTAGE
NPN SILICON TRANSISTOR



TO-39 CASE - MECHANICAL OUTLINE



LEAD CODE:

- 1) Emitter
- 2) Base
- 3) Collector

MARKING: FULL PART NUMBER

SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A (DIA)	0.335	0.370	8.51	9.40
B (DIA)	0.315	0.335	8.00	8.51
C	-	0.040	-	1.02
D	0.240	0.260	6.10	6.60
E	0.500	-	12.70	-
F (DIA)	0.016	0.021	0.41	0.53
G (DIA)	0.200		5.08	
H	0.100		2.54	
I	0.028	0.034	0.71	0.86
J	0.029	0.045	0.74	1.14

TO-39 (REV: R1)

R0 (27-August 2010)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms