


CFSH2-4L

**SURFACE MOUNT SILICON  
SCHOTTKY DIODE**



Top View Bottom View  
**SOD-882L CASE**



[www.centrasemi.com](http://www.centrasemi.com)

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CFSH2-4L is a high quality Schottky diode designed for applications where ultra small size and power dissipation are prime requirements. Packaged in an SOD-882L package, this component provides performance characteristics suitable for the most demanding size constrained applications.

**MARKING CODE: N**

**APPLICATIONS:**

- DC-DC converters
- Voltage clamping
- Protection circuits
- Battery powered devices including cell phones, digital cameras, pagers, PDAs, laptop computers, etc.

**MAXIMUM RATINGS:** ( $T_A=25^{\circ}\text{C}$ )

Peak Repetitive Reverse Voltage  
Average Forward Current  
Peak Forward Surge Current,  $t_p=8.3\text{ms}$   
Power Dissipation  
Operating Junction Temperature  
Storage Temperature  
Thermal Resistance

**FEATURES:**

- Device is **Halogen Free** by design
- Current ( $I_O=200\text{mA}$ )
- Low Forward Voltage Drop ( $V_F=0.53\text{V TYP @ }200\text{mA}$ )
- Low Reverse Current ( $350\text{nA TYP @ }40\text{V}$ )
- Small  $1\text{mm} \times 0.6\text{mm} \times 0.4\text{mm}$ , ultra low profile, Leadless Surface Mount package.

SYMBOL		UNITS
$V_{RRM}$	40	V
$I_O$	200	mA
$I_{FSM}$	1.0	A
$P_D$	100	mW
$T_J$	-65 to +125	$^{\circ}\text{C}$
$T_{stg}$	-65 to +150	$^{\circ}\text{C}$
$\theta_{JA}$	1000	$^{\circ}\text{C/W}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)




SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$I_R$	$V_R=10\text{V}$		0.08	1.0	$\mu\text{A}$
$I_R$	$V_R=40\text{V}$		0.35	2.0	$\mu\text{A}$
$BV_R$	$I_R=10\mu\text{A}$	40			V
$V_F$	$I_F=10\text{mA}$		0.33	0.45	V
$V_F$	$I_F=100\text{mA}$			0.52	V
$V_F$	$I_F=200\text{mA}$		0.53	0.60	V
$C_J$	$V_R=4.0\text{V}$ , $f=1.0\text{MHz}$		7.0	10	pF
$t_{rr}$	$I_F=I_R=10\text{mA}$ , $I_{rr}=1.0\text{mA}$ , $R_L=100\Omega$		5.0		ns

R6 (17-September 2015)

**CFSH2-4L**  
**SURFACE MOUNT SILICON**  
**SCHOTTKY DIODE**



**SOD-882L CASE - MECHANICAL OUTLINE**



\* Pin 1 chamfer may appear on any corner.

SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.037	0.041	0.95	1.05
B	0.022	0.026	0.55	0.65
C	0.026		0.65	
D	0.000	0.002	0.00	0.05
E	0.012	0.016	0.30	0.40
F	0.018	0.022	0.45	0.55
G	0.008	0.012	0.20	0.30

SOD-882L (REV:R2)

**LEAD CODE:**

- 1) Cathode
- 2) Anode

**MARKING CODE: N**







R2

R6 (17-September 2015)

**CFSH2-4L**  
**SURFACE MOUNT SILICON**  
**SCHOTTKY DIODE**



**TYPICAL ELECTRICAL CHARACTERISTICS**



R6 (17-September 2015)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)