

CMPZ4614
THRU
CMPZ4627

SURFACE MOUNT
LOW NOISE
SILICON ZENER DIODE
350mW, 5% TOLERANCE



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPZ4614 series devices are high quality silicon zener diodes designed for low leakage, low current and low noise applications.

MARKING CODE: SEE ELECTRICAL CHARACTERISTICS TABLE



SOT-23 CASE

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

Power Dissipation
Operating and Storage Junction Temperature

SYMBOL

P_D 350
 T_J, T_{stg} -65 to +150

UNITS

mW
 $^\circ\text{C}$



ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$ unless otherwise noted) $V_F=1.0\text{V MAX @ } I_F=200\text{mA}$ (for all types)

TYPE	NOMINAL ZENER VOLTAGE $V_Z @ I_{ZT}$	TEST CURRENT I_{ZT}	MAXIMUM ZENER IMPEDANCE $Z_{ZT} @ I_{ZT}$	MAXIMUM REVERSE LEAKAGE CURRENT		MAXIMUM ZENER CURRENT I_{ZM}	MAXIMUM NOISE DENSITY $N_D @ I_{ZT}$	MARKING CODE
	V	μA	Ω	μA	V	mA	$\mu\text{V}/\sqrt{\text{Hz}}$	
CMPZ4614	1.8	250	1200	7.5	1.0	120	1.0	C6A
CMPZ4615	2.0	250	1250	5.0	1.0	110	1.0	C6B
CMPZ4616	2.2	250	1300	4.0	1.0	100	1.0	C6C
CMPZ4617	2.4	250	1400	2.0	1.0	95	1.0	C6D
CMPZ4618	2.7	250	1500	1.0	1.0	90	1.0	C6E
CMPZ4619	3.0	250	1600	0.8	1.0	85	1.0	C6F
CMPZ4620	3.3	250	1650	7.5	1.5	80	1.0	C6G
CMPZ4621	3.6	250	1700	7.5	2.0	75	1.0	C6H
CMPZ4622	3.9	250	1650	5.0	2.0	70	1.0	C6J
CMPZ4623	4.3	250	1600	4.0	2.0	65	1.0	C6K
CMPZ4624	4.7	250	1550	10	3.0	60	1.0	C6L
CMPZ4625	5.1	250	1500	10	3.0	55	2.0	C6M
CMPZ4626	5.6	250	1400	10	4.0	50	4.0	C6N
CMPZ4627	6.2	250	1200	10	5.0	45	5.0	C6P

CMPZ4614
 THRU
 CMPZ4627
 SURFACE MOUNT
 LOW NOISE
 SILICON ZENER DIODE
 350mW, 5% TOLERANCE



SOT-23 CASE - MECHANICAL OUTLINE



LEAD CODE:
 1) Anode
 2) No Connection
 3) Cathode

DIMENSIONS				
SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.003	0.007	0.08	0.18
B	0.006	-	0.15	-
C	-	0.005	-	0.13
D	0.035	0.044	0.89	1.12
E	0.110	0.120	2.80	3.05
F	0.075		1.90	
G	0.037		0.95	
H	0.047	0.055	1.19	1.40
I	0.083	0.104	2.10	2.64
J	0.014	0.020	0.35	0.50

SOT-23 (REV: R4)

R8 (25-February 2019)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms