


CP379X-7002AHC

N-Channel MOSFET Die

Enhancement-Mode

The CP379X-7002AHC is a high current silicon N-Channel MOSFET designed for high speed pulsed amplifier and driver applications.



MECHANICAL SPECIFICATIONS:

Die Size	31.5 x 31.5 MILS
Die Thickness	5.5 MILS
Gate Bonding Pad Size	3.9 x 3.9 MILS
Source Bonding Pad Size	19.3 x 21.3 MILS
Top Side Metalization	Al-Si – 35,000Å
Back Side Metalization	Au – 9,000Å
Scribe Alley Width	2.76 MILS
Wafer Diameter	6 INCHES
Gross Die Per Wafer	23,600

MAXIMUM RATINGS: ($T_A=25^{\circ}\text{C}$)

	SYMBOL		UNITS
Drain-Source Voltage	V_{DS}	60	V
Drain-Gate Voltage	V_{DG}	60	V
Gate-Source Voltage	V_{GS}	20	V
Continuous Drain Current (Steady State)	I_D	1.0	A
Maximum Pulsed Drain Current ($t_p=10\mu\text{s}$)	I_{DM}	5.0	A
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	$^{\circ}\text{C}$






ELECTRICAL CHARACTERISTICS: ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I_{GSSF}, I_{GSSR}	$V_{GS}=20\text{V}, V_{DS}=0$			10	μA
I_{DSS}	$V_{DS}=60\text{V}, V_{GS}=0$			500	nA
BV_{DSS}	$V_{GS}=0, I_D=100\mu\text{A}$	63			V
$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1.2		2.3	V
V_{SD}	$V_{GS}=0, I_S=500\text{mA}$			0.9	V
$r_{DS(ON)}$	$V_{GS}=10\text{V}, I_D=500\text{mA}$			0.22	Ω
$r_{DS(ON)}$	$V_{GS}=5.0\text{V}, I_D=500\text{mA}$			0.30	Ω
$Q_{g(tot)}$	$V_{DS}=10\text{V}, V_{GS}=4.5\text{V}, I_D=1.0\text{A}$		2.3		nC
Q_{gs}	$V_{DS}=10\text{V}, V_{GS}=4.5\text{V}, I_D=1.0\text{A}$		1.0		nC
Q_{gd}	$V_{DS}=10\text{V}, V_{GS}=4.5\text{V}, I_D=1.0\text{A}$		0.7		nC
C_{rss}	$V_{DS}=25\text{V}, V_{GS}=0, f=1.0\text{MHz}$			25	pF
C_{iss}	$V_{DS}=25\text{V}, V_{GS}=0, f=1.0\text{MHz}$			240	pF
C_{oss}	$V_{DS}=25\text{V}, V_{GS}=0, f=1.0\text{MHz}$			50	pF
t_{on}	$V_{DD}=30\text{V}, V_{GS}=4.5\text{V}, I_D=1.0\text{A}$ $R_G=6.0\Omega, R_L=30\Omega$			35	ns
t_{off}	$V_{DD}=30\text{V}, V_{GS}=4.5\text{V}, I_D=1.0\text{A}$ $R_G=6.0\Omega, R_L=30\Omega$			50	ns

R0 (27-August 2018)

CP379X-7002AHC

Typical Electrical Characteristics



BARE DIE PACKING OPTIONS



BARE DIE IN TRAY (WAFFLE) PACK

CT: Singulated die in tray (waaffle) pack.
(example: CP211-PART NUMBER-CT)

CM: Singulated die in tray (waaffle) pack 100% visually inspected as per MIL-STD-750, (method 2072 transistors, method 2073 diodes).
(example: CP211-PART NUMBER-CM)



UNSAWN WAFER

WN: Full wafer, unsawn, 100% tested with reject die inked.
(example: CP211-PART NUMBER-WN)



SAWN WAFER ON PLASTIC RING

WR: Full wafer, sawn and mounted on plastic ring,
100% tested with reject die inked.
(example: CP211-PART NUMBER-WR)

Please note: Sawn Wafer on Metal Frame (WS) is possible as a special order. Please contact your Central Sales Representative at 631-435-1110.



Visit the Central website for a complete listing of specifications:
www.centrasemi.com/bdspecs

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms