


The CPZ28X-1N4099 thru CPZ28X-1N4135 are silicon Zener diodes ideal for all types of commercial, industrial, entertainment, and computer applications.



**MECHANICAL SPECIFICATIONS:**

|                        |                 |
|------------------------|-----------------|
| Die Size               | 13 x 13 MILS    |
| Die Thickness          | 5.5 MILS        |
| Anode Bonding Pad Size | 7.0 x 7.0 MILS  |
| Top Side Metalization  | Ti/Al – 13,000Å |
| Back Side Metalization | Au-As – 9,000Å  |
| Scribe Alley Width     | 1.97 MILS       |
| Wafer Diameter         | 5 INCHES        |
| Gross Die Per Wafer    | 101,184         |

**MAXIMUM RATINGS:**

Operating and Storage Junction Temperature

**SYMBOL**

$T_J, T_{stg}$

-65 to +150

**UNITS**

°C

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$ )  $V_F=1.1\text{V MAX @ } I_F=200\text{mA}$  (for all types)

| Type          | Zener Voltage<br>$V_Z @ I_{ZT}$ |     |       | Test Current<br>$I_{ZT}$ | Maximum Zener Impedance<br>$Z_{ZT} @ I_{ZT}$ | Maximum Reverse Current |      | Maximum Zener Current<br>$I_{ZM}$ | Maximum Noise Density<br>$N_D @ 250\mu\text{A}$ |
|---------------|---------------------------------|-----|-------|--------------------------|--|-------------------------|------|-----------------------------------|---|
|               | MIN                             | NOM | MAX   |                          |  | $I_R @ V_R$             |      |                                   |   |
|               | V                               | V   | V     |                          |  | $\mu\text{A}$           | V    |                                   |   |
| CPZ28X-1N4099 | 6.460                           | 6.8 | 7.140 | 250                      | 200  | 10                      | 5.2  | 35.0                              | 40  |
| CPZ28X-1N4100 | 7.125                           | 7.5 | 7.875 | 250                      | 200  | 10                      | 5.7  | 31.8                              | 40  |
| CPZ28X-1N4101 | 7.790                           | 8.2 | 8.610 | 250                      | 200  | 1.0                     | 6.3  | 29.0                              | 40  |
| CPZ28X-1N4102 | 8.265                           | 8.7 | 9.135 | 250                      | 200  | 1.0                     | 6.7  | 27.4                              | 40  |
| CPZ28X-1N4103 | 8.645                           | 9.1 | 9.555 | 250                      | 200  | 1.0                     | 7.0  | 26.2                              | 40  |
| CPZ28X-1N4104 | 9.50                            | 10  | 10.50 | 250                      | 200  | 1.0                     | 7.6  | 24.8                              | 40  |
| CPZ28X-1N4105 | 10.45                           | 11  | 11.55 | 250                      | 200  | 0.05                    | 8.5  | 21.6                              | 40  |
| CPZ28X-1N4106 | 11.40                           | 12  | 12.60 | 250                      | 200  | 0.05                    | 9.2  | 20.4                              | 40  |
| CPZ28X-1N4107 | 12.35                           | 13  | 13.65 | 250                      | 200  | 0.05                    | 9.9  | 19.0                              | 40  |
| CPZ28X-1N4108 | 13.30                           | 14  | 14.70 | 250                      | 200  | 0.05                    | 10.7 | 17.5                              | 40  |
| CPZ28X-1N4109 | 14.25                           | 15  | 15.75 | 250                      | 100  | 0.05                    | 11.4 | 16.3                              | 40  |
| CPZ28X-1N4110 | 15.20                           | 16  | 16.80 | 250                      | 100  | 0.05                    | 12.2 | 15.4                              | 40  |
| CPZ28X-1N4111 | 16.15                           | 17  | 17.85 | 250                      | 100  | 0.05                    | 13.0 | 14.5                              | 40  |
| CPZ28X-1N4112 | 17.10                           | 18  | 18.90 | 250                      | 100  | 0.05                    | 13.7 | 13.2                              | 40  |
| CPZ28X-1N4113 | 18.05                           | 19  | 19.95 | 250                      | 150  | 0.05                    | 14.5 | 12.5                              | 40  |
| CPZ28X-1N4114 | 19.00                           | 20  | 21.00 | 250                      | 150  | 0.01                    | 15.2 | 11.9                              | 40  |
| CPZ28X-1N4115 | 20.90                           | 22  | 23.10 | 250                      | 150  | 0.01                    | 16.8 | 10.8                              | 40  |
| CPZ28X-1N4116 | 22.80                           | 24  | 25.20 | 250                      | 150  | 0.01                    | 18.3 | 9.9                               | 40  |
| CPZ28X-1N4117 | 23.75                           | 25  | 26.25 | 250                      | 150  | 0.01                    | 19.0 | 9.5                               | 40  |
| CPZ28X-1N4118 | 25.65                           | 27  | 28.35 | 250                      | 150  | 0.01                    | 20.5 | 8.8                               | 40  |

R0 (26-June 2017)

**CPZ28X-1N4099 THRU  
CPZ28X-1N4135  
Zener Diode Die  
250mW, 6.8 THRU 100 VOLT**

**ELECTRICAL CHARACTERISTICS - Continued: ( $T_A=25^\circ\text{C}$ )  $V_F=1.1\text{V MAX @ } I_F=200\text{mA}$  (for all types)**

| Type          | Zener Voltage<br>$V_Z @ I_{ZT}$ |     |       | Test Current  | Maximum Zener Impedance | Maximum Reverse Current |      | Maximum Zener Current | Maximum Noise Density          |
|---------------|---------------------------------|-----|-------|---------------|-------------------------|-------------------------|------|-----------------------|--------------------------------|
|               | MIN                             | NOM | MAX   | $I_{ZT}$      | $Z_{ZT} @ I_{ZT}$       | $I_R @ V_R$             |      | $I_{ZM}$              | $N_D @ 250\mu\text{A}$         |
|               | V                               | V   | V     | $\mu\text{A}$ | $\Omega$                | $\mu\text{A}$           | V    | mA                    | $\mu\text{V}/\sqrt{\text{Hz}}$ |
| CPZ28X-1N4119 | 26.60                           | 28  | 29.40 | 250           | 200                     | 0.01                    | 21.3 | 8.5                   | 40                             |
| CPZ28X-1N4120 | 28.50                           | 30  | 31.50 | 250           | 200                     | 0.01                    | 22.8 | 7.9                   | 40                             |
| CPZ28X-1N4121 | 31.35                           | 33  | 34.65 | 250           | 200                     | 0.01                    | 25.1 | 7.2                   | 40                             |
| CPZ28X-1N4122 | 34.20                           | 36  | 37.80 | 250           | 200                     | 0.01                    | 27.4 | 6.6                   | 40                             |
| CPZ28X-1N4123 | 37.05                           | 39  | 40.95 | 250           | 200                     | 0.01                    | 29.7 | 6.1                   | 40                             |
| CPZ28X-1N4124 | 40.85                           | 43  | 45.15 | 250           | 250                     | 0.01                    | 32.7 | 5.5                   | 40                             |
| CPZ28X-1N4125 | 44.65                           | 47  | 49.35 | 250           | 250                     | 0.01                    | 35.8 | 5.1                   | 40                             |
| CPZ28X-1N4126 | 48.45                           | 51  | 53.55 | 250           | 300                     | 0.01                    | 38.8 | 4.6                   | 40                             |
| CPZ28X-1N4127 | 53.20                           | 56  | 58.80 | 250           | 300                     | 0.01                    | 42.6 | 4.2                   | 40                             |
| CPZ28X-1N4128 | 57.00                           | 60  | 63.00 | 250           | 400                     | 0.01                    | 45.6 | 4.0                   | 40                             |
| CPZ28X-1N4129 | 58.90                           | 62  | 65.10 | 250           | 500                     | 0.01                    | 47.1 | 3.8                   | 40                             |
| CPZ28X-1N4130 | 64.60                           | 68  | 71.40 | 250           | 700                     | 0.01                    | 51.7 | 3.5                   | 40                             |
| CPZ28X-1N4131 | 71.25                           | 75  | 78.75 | 250           | 700                     | 0.01                    | 57.0 | 3.1                   | 40                             |
| CPZ28X-1N4132 | 77.90                           | 82  | 86.10 | 250           | 800                     | 0.01                    | 62.4 | 2.9                   | 40                             |
| CPZ28X-1N4133 | 82.65                           | 87  | 91.35 | 250           | 1.0K                    | 0.01                    | 66.2 | 2.7                   | 40                             |
| CPZ28X-1N4134 | 86.45                           | 91  | 95.55 | 250           | 1.2K                    | 0.01                    | 69.2 | 2.6                   | 40                             |
| CPZ28X-1N4135 | 95.00                           | 100 | 105.0 | 250           | 1.5K                    | 0.01                    | 76.0 | 2.3                   | 40                             |

## BARE DIE PACKING OPTIONS

---



### BARE DIE IN TRAY (WAFFLE) PACK

**CT:** Singulated die in tray (waffle) pack.  
(example: CP211-PART NUMBER-CT)

**CM:** Singulated die in tray (waffle) pack 100% visually inspected as per MIL-STD-750, (method 2072 transistors, method 2073 diodes).  
(example: CP211-PART NUMBER-CM)

---



### UNSAWN WAFER

**WN:** Full wafer, unsawn, 100% tested with reject die inked.  
(example: CP211-PART NUMBER-WN)

---



### SAWN WAFER ON PLASTIC RING

**WR:** Full wafer, sawn and mounted on plastic ring,  
100% tested with reject die inked.  
(example: CP211-PART NUMBER-WR)

Please note: Sawn Wafer on Metal Frame (WS) is possible as a special order. Please contact your Central Sales Representative at 631-435-1110.



Visit the Central website for a complete listing of specifications:  
[www.centrasemi.com/bdspecs](http://www.centrasemi.com/bdspecs)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)



# Product End of Life Notification

|                            |            |
|----------------------------|------------|
| <b>PDN ID:</b>             | PDN01257   |
| <b>Notification Date:</b>  | 5/31/23    |
| <b>Last Buy Date:</b>      | Stock Only |
| <b>Last Shipment Date:</b> | Stock Only |

<https://www.centrasemi.com>

Please be advised that Central Semiconductor must immediately discontinue the product(s) listed in the attached PDN notice. Orders can only be accepted for products with available inventory on hand.

You may have purchased one or more of the products listed. Please do not hesitate to contact your local Central Semiconductor sales representative with any questions or needs you may have. Central regrets any inconvenience this may cause.

Sincerely,

Central Semiconductor Corp.

---

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



<https://www.centrasemi.com>

# Product End of Life Notification

|                    |            |
|--------------------|------------|
| PDN ID:            | PDN01257   |
| Notification Date: | 5/31/23    |
| Last Buy Date:     | Stock Only |
| Last Shipment Date | Stock Only |

Summary: The CPZ28X chip process is discontinued and the following items are now classified as End of Life (EOL).

Although Central Semiconductor makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Portfolio Management. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

**\* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.**

| Central Part Number | Suggested Replacement |
|---------------------|-----------------------|
| CPZ28X-BZX55C3V3-CM | CPZ58X-BZX55C3V3-CM   |
| CPZ28X-BZX55C3V3-CT | CPZ58X-BZX55C3V3-CT   |
| CPZ28X-BZX55C3V3-WN | CPZ58X-BZX55C3V3-WN   |
| CPZ28X-BZX55C6V8-CT | CPZ58X-BZX55C6V8-CT   |
| CPZ28X-BZX55C6V8-WN | CPZ58X-BZX55C6V8-WN   |
| CPZ28X-BZX84B5V1-CT | CPZ58X-BZX84B5V1-CT   |
| CPZ28X-BZX84B5V1-WN | CPZ58X-BZX84B5V1-WN   |
| CPZ28X-CMPZ5226B-WR | CPZ58X-CMPZ5226B-WR   |
| CPZ28X-CMPZ5235B-CT | CPZ58X-CMPZ5235B-CT   |
| CPZ28X-CMPZ5235B-WN | CPZ58X-CMPZ5235B-WN   |
| CPZ28X-C5235B-CT20  | N/A                   |
| CPZ28X-1N4099-CT    | CPZ58X-1N4099-CT      |
| CPZ28X-1N4099-WN    | CPZ58X-1N4099-WN      |
| CPZ28X-1N4623-CT    | CPZ58X-1N4623-CT      |
| CPZ28X-1N4623-WN    | CPZ58X-1N4623-WN      |
| CPZ28X-1N4692-CT    | CPZ58X-1N4692-CT      |
| CPZ28X-1N4692-WN    | CPZ58X-1N4692-WN      |
| CPZ28X-1N5237B-CT   | CPZ58X-1N5237B-CT     |
| CPZ28X-1N968B-WN    | CPZ59X-1N968B-WN      |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit <https://my.centrasemi.com/submit-inquiry?type=ER> to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.