

[www.centrasemi.com](http://www.centrasemi.com)

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CT-32 silicon DIAC functions as a trigger diode with a fixed voltage reference and low breakover current. This device is manufactured in a hermetically sealed glass package to ensure high reliability.

**MAXIMUM RATINGS:** ( $T_A=25^{\circ}\text{C}$ )

Peak Repetitive On-state Current,  $t_p=20\mu\text{s}$ ,  $f=120\text{Hz}$   
Operating and Storage Junction Temperature

SYMBOL	UNITS
$I_{TRM}$	A
$T_J, T_{stg}$	$^{\circ}\text{C}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^{\circ}\text{C}$ )

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
$I_R$	$V_R=18\text{V}$		10	$\mu\text{A}$
$I_{BO}$	$C=22\text{nF}^*$		50	$\mu\text{A}$
$I_P$	(see Figure 2)		0.3	A
$V_{BO}^{**}$	$C=22\text{nF}^*$	28	36	V
$ V_{BO1}-V_{BO2} $	$C=22\text{nF}^*$		3.0	V
$\Delta V$	$V_{BO}$ & $V_F$ @ 10mA	5.0		V
$V_O$	(see Figure 2)	5.0		V
$t_r$	(see Figure 3)		2.0	$\mu\text{s}$

\*Capacitor connected in parallel with device.  
\*\*Both directions.

**CT-32**

**SILICON DIAC**




Figure 1. Voltage – Current Characteristic Curve




Figure 2. Test Circuit





Figure 3. Rise Time Measurement

**DO-35 CASE - MECHANICAL OUTLINE**



DIMENSIONS				
SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.018	0.022	0.46	0.56
B	0.120	0.200	3.05	5.08
C	0.060	0.090	1.52	2.29
D	1.000	-	25.40	-

DO-35 (REV: R1)

R1 (26-June 2012)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)



<http://www.centrasemi.com>

## Product End of Life Notification

<b>PDN ID:</b>	PDN01017
<b>Notification Date:</b>	1/29/16
<b>Last Buy Date:</b>	7/29/16
<b>Last Shipment Date</b>	1/29/17

Summary: The CT-32 silicon DIAC packaged in the DO-35 case is being discontinued due to low demand and is now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

<b><u>Central Part Number</u></b>	<b><u>Replacement</u></b>
CT-32 BK	N/A
CT-32 TR	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to [engineering@centrasemi.com](mailto:engineering@centrasemi.com).

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.