

Small Signal NPN Transistors

TO-72 Case



TYPE NO.	DESCRIPTION	V_{CBO}	V_{CEO}	V_{EBO}	I_{CBO}	V_{CB}	h_{FE}		I_C	V_{CE}	$V_{CE(SAT)}$		f_T	C_{ob}
		(V)	(V)	(V)	(μA)	(V)	MIN	MAX	(mA)	(V)	(V)	(mA)	(MHz)	(* C_{cb})
		MIN	MIN	MIN	MAX						MAX		MIN	MAX
2N917	RF/IF OSCILLATOR	30	15	3.0	0.001	15	20	--	3.0	1.0	0.5	3.0	500	1.7
2N917A	RF/IF OSCILLATOR	30	15	3.0	--	--	20	200	3.0	10	--	--	600	1.7
2N918	RF/IF OSCILLATOR	30	15	3.0	0.01	15	20	--	3.0	1.0	0.4	10	600	1.7
2N998	DARLINGTON	100	60	15	0.01	90	1,600	8,000	10	5.0	1.8	100	60	30
2N2857	VHF/UHF OSC	30	15	2.5	0.01	15	30	150	3.0	1.0	--	--	1,000	1.0*
2N2865	RF/IF OSCILLATOR	25	13	3.0	0.01	15	20	200	4.0	10	0.4	10	600	2.5
2N3478	VHF/UHF LOW NOISE	30	15	2.0	0.02	1.0	25	150	2.0	8.0	--	--	750	1.0*
2N3839	VHF/UHF AMPL/OSC	30	15	2.5	0.01	15	30	150	3.0	1.0	--	--	1,000	1.0*
2N5179	VHF/UHF AMPL/OSC	20	12	2.5	0.02	15	25	250	3.0	1.0	0.4	10	900	1.0*
BFY90	VHF/UHF AMPL/OSC	30	15	2.5	0.01	15	20	125	25	1.0	--	--	1,000	1.5*

Shaded areas indicate Darlington.

Dual Transistors

TO-71 Case

P_D @ $T_A=25^\circ C=360mW$ Total (Both Die Equal Power)



TYPE NO.	DESCRIPTION	V_{CBO}	V_{CEO}	V_{EBO}	I_{CBO}	V_{CB}	h_{FE}		I_C	V_{CE}	$V_{CE(SAT)}$		MATCHING	
		(V)	(V)	(V)	(nA)	(V)	MIN	MAX	(mA)	(V)	(V)	(mA)	h_{FE}	V_{BE}
		MIN	MIN	MIN	MAX						MAX		%	(mV)
CEN741	NPN LOW NOISE	45	45	6.0	10	45	150	600	0.01	5.0	0.35	1.0	20	5.0
CEN832	PNP LOW NOISE	60	60	5.0	10	50	150	450	1.0	5.0	0.25	1.0	20	5.0

(6-December 2004)

Central
Semiconductor Corp.
www.centalsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms