CMPP6027R CMPP6028R

SURFACE MOUNT SILICON PROGRAMMABLE UNIJUNCTION TRANSISTORS



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPP6027R and CMPP6028R are silicon programmable unijunction transistors, manufactured in a surface mount SOT-23 package, designed for adjustable (programmable) characteristics such as, valley current (I $_V$), peak current (I $_P$), and intrinsic standoff ratio ($_1$).

MARKING CODES: CMPP6027R: P27

CMPP6028R: P28



MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Gate-Cathode Forward Voltage	V_{GKF}	40	V
Gate-Cathode Reverse Voltage	V_{GKR}	5.0	V
Gate-Anode Reverse Voltage	V_{GAR}	40	V
Anode-Cathode Voltage	V_{AK}	40	V
Peak Non-Repetitive Forward Current (t=10µs)	ITSM	5.0	Α
Peak Repetitive Forward Current (t=20µs, D.C.=1.0%)	I _{TRM}	2.0	Α
Peak Repetitive Forward Current (t=100µs, D.C.=1.0%)	ITRM	1.0	Α
DC Forward Anode Current	lΤ	150	mA
DC Gate Current	I_{G}	50	mA
Power Dissipation (Note 1)	P_{D}	167	mW
Storage Temperature	T _{stg}	-55 to +150	°C
Operating Junction Temperature	T_J	-50 to +100	°C
Thermal Resistance (Note 1)	$\Theta_{\sf JA}$	450	°C/W

Note 1: Mounted on 2 inch square FR-4 PCB with minimum copper pad area.

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

		CMPP	6027R	CMPP	6028R	
SYMBOL	TEST CONDITIONS	MIN	MAX	MIN	MAX	UNITS
I _{GAO}	V _S =40V		10		10	nA
I _{GKS}	V _S =40V		50		50	nA
lΡ	V_S =10V, R_G =1.0M Ω		2.0		0.15	μΑ
lΡ	$V_S=10V$, $R_G=10k\Omega$		5.0		1.0	μΑ
lV	V_S =10V, R_G =1.0M Ω		50		25	μΑ
lV	$V_S=10V$, $R_G=10k\Omega$	70		25		μΑ
lV	V_S =10V, R_G =200 Ω	1.5		1.0		mA
V_{T}	V_S =10V, R_G =1.0M Ω	0.2	1.6	0.2	0.6	V
V_{T}	$V_S=10V$, $R_G=10k\Omega$	0.2	0.6	0.2	0.6	V
V_{F}	I _F =50mA		1.5		1.5	V
V_{O}	$V_B = 20V, C_C = 0.2 \mu F$	6.0		6.0		V
t_r	$V_B = 20V, C_C = 0.2 \mu F$		80		80	ns


R0 (24-June 2015)


CMPP6027R CMPP6028R

SURFACE MOUNT SILICON PROGRAMMABLE UNIJUNCTION TRANSISTORS



SOT-23 CASE - MECHANICAL OUTLINE





LEAD CODE:

- 1) Anode
- 2) Cathode
- 3) Gate

MARKING CODES: CMPP6027R: P27 CMPP6028R: P28

DIMENSIONS					
	INCHES		MILLIMETERS		
SYMBOL	MIN	MAX	MIN	MAX	
А	0.003	0.007	0.08	0.18	
В	0.006	-	0.15	-	
С	-	0.005	-	0.13	
D	0.035	0.043	0.89	1.09	
E	0.110	0.120	2.80	3.05	
F	0.075		1.90		
G	0.037		0.95		
Н	0.047	0.055	1.19	1.40	
	0.083	0.098	2.10	2.49	
J	0.014	0.020	0.35	0.50	

SOT-23 (REV: R3)

R0 (24-June 2015)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)



Product End of Life Notification

PDN ID:	PDN01109 Rev:001
Notification Date:	3/28/23
Last Buy Date:	N/A
Last Shipment Date	N/A

Summary: The CMPP6027R and CMPP6028R Programmable UJTs are discontinued and now classified as End of Life (EOL). Rev:001 of PDN#01109, March 28, 2023, issued to remove CMPP6028R BK and CMPP6028R TR to address market demand; CMPP6028R BK and CMPP6028R TR are now active devices.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Portfolio Management. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

Central Part Number	Suggested Replacement
CMPP6027R BK	N/A
CMPP6027R TR	N/A
CMPP6028R BK	Item CMPP6028R BK removed from PDN; device now active.
CMPP6028R TR	Item CMPP6028R TR removed from PDN; device now active.

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit https://my.centralsemi.com/submit-inquiry?type=ER to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002